

CFS Floor Level Convectors

CI/SfB

56

TS 45



Applications

A range of low profile floor level convectors for inconspicuous perimeter heating often used in offices, meeting rooms, reception areas, under pew heating in churches and for anti frost protection. Ideal where a noise free reliable heater is required.


Features

- rugged low profile 22 gauge steel cabinet.
- noise free, centrally fixed element with floating ends.
- long life, aluminium finned stainless steel element.
- quick heat up and efficient heat distribution
- multi hole mounting for quick installation.
- scuff resistant textured ivory powder coated finish.(RAL9002)
- over temperature safety cut-out along full length of element.
- optional integral thermostat.
- optional integral tamperproof thermostat.

Installation [Download full installation instructions at www.ceh ltd.co.uk](http://www.ceh ltd.co.uk)

Fixed at low level as single units or as part of a full wall length installation. Multi hole fixing for ease of mounting. The unit should be securely fixed and electrical connection made by a suitably qualified person in accordance with the latest edition of the IEE requirements for Electrical Installation (BS7671:2001). Temperature control by remote or integral thermostat.

Specification



Cat No	Watts at 240v	Length (mm)	Wt.(kgs)
CFS-0375	375	610	3.0
CFS-0500	500	712	3.5
CFS-0750	750	1016	4.0
CFS-1000	1000	1220	5.5
CFS-1250	1250	1525	6.0
CFS-1500	1500	1830	8.0
CFS-2000	2000	2440	11.5
CFS-TB	Integral Thermostat		
CFS-TTB	Integral Tamperproof Thermostat		

The manufacturers reserve the right to change the specification without prior notice E&OE





Commercial Electric Heat Limited
Unit 712 Thorp Arch Trading Estate
Wetherby West Yorkshire LS23 7FF
Tel 01937 844994 Fax 01937 844123
www.ceh ltd.co.uk
email sales@ceh ltd.co.uk