

Heater controls

CI/SfB

56


TS 213

Thermostats

Most of our heaters can be supplied with integral thermostats, they are activated by the temperature sensed close to the heater. A more accurate control of the environmental temperature is achieved with a remote thermostat some of which have additional features to give a more energy efficient installation.


CRST16 Interior Room Thermostat

Range +10°C/+30°C
Rating 16A 230Vac
Protection class IP20




CTRT-10 Tamperproof Interior Room Thermostat

Range +6°C/+30°C
Rating 10A 230Vac
Protection class IP20




CFST Interior Frost Thermostat

Range -5°C/+15°C
Rating 16A 230Vac
Protection class IP20




CXFST Exterior Frost Thermostat

Range -5°C/+25°C
Rating 10A 230Vac
Protection class IP65




CPRST Programmable Interior Room Thermostat

Weekday/Weekend operation
4 on/off settings per day
Fixed Frost protection setting
Permanent on/off or timed selection
Range +5°C/+35°C
Rating 5A 230Vac
Protection class IP20



CPRSTW Programmable Wireless Room Thermostat


433 MHz RF Control 100m open site range
LCD Display
Weekday/Weekend operation
4 on/off settings per day
Fixed Frost protection setting
Permanent on/off or timed selection
Range +5°C/+35°C Rating 16A 230Vac
Protection class IP20



Time controllers


CTCM Electro Mechanical Time controller

24 hour or 7 day operation
Manual override and permanent on/off
10 on /10 off settings per 24 hour period
20 minutes minimum switching interval for 24 hour operation
2 hour minimum switching interval for 7 day operation
Single pole volt free contacts.
Rating 20A 230Vac
Protection class IP20




CTCD DigitalTime controller

24 hour - 7 day,
Easy text oriented programming with battery back up.
Manual override and permanent on/off
21 on /21off settings per 7day period
1 minute minimum switching period
Change over volt free contacts.
Rating 16A 230Vac
Protection class IP20



CTTF 7 day Fused Time controller


Incorporates 13A fused connection unit fitting to single gang wall box(25mm)
Easy two button programming with battery back up.
Manual override and permanent on/off
21 on /21off settings per 7day period
1 minute minimum switching period
Single pole volt free contacts.
Rating 13A 230Vac
Protection class IP20



PIR Controller

CPIR Passive Infra Red movement sensor

12m detection range with 180° area of detection
Adjustable ON time 5 sec to 12 mins
Manual ON/OFF override
Rating 16A 230Vac
Protection class IP44



The manufacturers reserve the right to change the specification without prior notice E&OE



Commercial Electric Heat Limited
Unit 712 Thorp Arch Trading Estate
Wetherby West Yorkshire LS23 7FF
Tel 01937 844994 Fax 01937 844123
www.cehltd.co.uk
email sales@cehltd.co.uk